




RONGTA

RP400

THERMAL TRANSFER BARCODE PRINTER



RP 400



Hospital



Logistics



Jewelry



Postal



Bank



Market



Convenience
Store



Dining



RONGTA TECHNOLOGY (XIAMEN) GROUP CO., LTD.

WWW.RONGTATECH.COM



RP400--Thermal Transfer Barcode Printer

- Fashion appearance
- With high speed, excellent stability and durability
- Paper detection by transmission type, accurately and rapidly
- Powerful function, support parallel, serial, USB multiple interfaces
- Imported thermal printer head, printing clearly and stable
- With function for automatic correction paper and carbon

Item

Thermal Transfer Barcode Printer RP400

Printing

Resolution	203dpi (High Resolution and High Speed)
Printing method	Thermal Transfer/Direct Thermal
Printing speed	4-5 Inch/s
Max printing width	104mm (4.09')
Max printing Length	2286mm (90')
Interface	USB/ (USB+ Serial+Parallel+Ethernet)
Commands	TSC
Ribbon Length	Max 300M
Ribbon width	Min. 30mm; Max. 110mm

Media

Max Media Roll OD	127mm (5")
Min Media Roll ID	25mm
Media Paper Type	Continuous, gap, fan fold, black mark,
Media Rolling Up Method	Printing side outward Rolling
Media width	Max 120mm (4.72"), Min: 20mm (0.78")
Media Roll Core Size	25.4mm~38mm
Media Gap	Min.2mm
Media Thickness	0.058mm~0.305mm
Label Length	10mm~2286mm
Accessories	External Media Holder (Optional)

Software

Editing Software	Nicelabel SE
Driver	Windows 2000, XP, Vista, Win7, Win8, Windows Server 2003&2008

Character font

Character Set	Nicelabel SE
Print font	ASCII Font A: 12*24 ASCII Font B: 9*24 Chinese: 24*24

Environment Specification

Temperature	Working: 5-45°C, Storage: -10~50°C
Humidity	Working : 25%~85% ; Storage: 10%~90%

Power supply

Input: AC 100V/240V, Output: DC24V/2.5A,50/60W

Storage

8MB FLASH/8MB SDRAM

