



RONGTA PORTABLE LABEL PRINTER RPP-04 BWU 4 INCH

Print	Printing Method	Thermal Line
	Effective Printing Width	104mm (MAX)
	Resolution	203dpi
	Printing Speed	50mm/s
	Printing Density	
	Character set	GB18030 (Simplified Chinese)
	Print Font	ASCII Font A : 12×24 ASCII Font B : 9×17 Chinese: 24×24
	Character per line	
Paper Spec	Paper Type	
	Paper Width	40-110mm
	Paper Roll Diameter	Φ 50mm (MAX)
	Paper loading	Easy paper loading
	Paper out detection	Support
Barcodes	Barcode type	Code 39, 39C, I25, Code 93, ITF25, EAN128, Code 128, Codabar, EAN-8, EAN8+2, EAN8+5, EAN-13, EAN13+2, EAN13+5, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5 MSIC, ITF14, EAN14, CODE11, POST QRCODE, PDF417 (Optional)
Reliability	MCBF(MCBF)	NA
	Cutter Life	NA
	Printer Head Life	50km Printing length
Interface		WU, BU, BWU
RAM		8MB
FLASH		
Printing Command		ESC/POS/TSPL/CPCL/ZPL
Battery		7.4V, 2400mAH
Certificate		CE, IP54
Physical	Printer Dimension (LxWxH)	133×149×60mm
	Weight	0.58kg
Environment	Working Environment	temperature: 0~45°C humidity: 20-90%
	Srorage Environment	temperature: -10~60 °C humidity: 10-90% (paper excluded)