

XL-2360A

2D Desktop Barcode Scanner

Big scan window

Strong decoding capacity

Ultra long depth of field



1D/2D



Auto



1280x800Pixels



32-bit ARM



Mobile payment



Alipay payment



WeChat payment

Applications



Features

- ◆ Support USB, USB-VCOM, RS-232 interface
- ◆ Wide scan window, full 360-degree coverage scanning
- ◆ CMOS image technology, quick reading commodity codes and screen codes
- ◆ Super decoding ability of all kinds of colored, stained and damaged barcodes
- ◆ Automatic induction in the effective recognition range
- ◆ 3mm thick float glass, resistant to old wear, dust, and shock

SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390 Website: www.xl-scan.com E-mail: overseas01@xl-scan.cn



XL-2360A

Technical Parameters

Performance Parameter

CPU	32bit ARM
Light Source	Red LED (Lighting) Color
Scan Mode	Continue scanning & Automatic induction
Image Size	1280x800 Pixels
Scanning Speed	60 fps/s
Mnimum Resolution	≥3mil
Decoding Depth	0~400mm@(13mil EAN 13)
Print Contrast	≥10%
Decoding Capability	1D: Codabar、Code39、Code32、Interleaved 2 of 5、Industrial 2 of 5、Matrix 2 of 5、Code11、Code128、GS1-128、UPC-A、UPC-E、EAN/JAN-8、EAN/JAN-13、ISBN、ISSN、Gs1 DataBar、GS1 DataBar Limited、GS1 DataBar Expanded、MSI、Febraban etc. 2D: PDF417、Micro PDF417、QR Code、Micro QR、Data Matrix、Aztec Code



Other Parameters

Size	L × W × H: 149.8×88×132.6(mm)
Weight	841g (Including cable)
Case Material	ABS+PC
Cable	Straight 2m
Input Voltage	DC 5V
Stand-by Current	≤210mA
Working Current	≤500mA
Indicator	Buzzer, indicator light
Interface	USB-HID、RS-232、USB-VCP
Temperature (Operating)	-10°C~50°C
Humidity	5% to 95% (non-condensing)
Temperature (Storage)	-20°C~60°C

*XL-2360A-02/23B-V.1.0.0

